# Security - Protection - Prevention





## **Security - Protection - Prevention**

# **Bulletproof Armored**Security Door

KETE Bulletproof Armored Security Door can be used in a wide variety of applications:





- Double armored door leaf made of electro galvanized metal sheet.
- Special bulletproof material.
- Frame with embedded false frame electrostatic painted in RAL 9005 black anti-scratch.
- Four heavy type adjustable hinges.
- Limiting opening device for controlled opening.
- Latch regulator.
- Automatic Door Bottom Seal.
- Full perimeter rubber gasket for the frame.

#### **Standardized Nominal Dimensions**

**Width:** 93/98/103 cm **Height:** 208/212/216 cm

Special dimensions per 5 cm in width and per 4 cm in height, with minimum width 68 cm and maximum 123 cm and height minimum of 192 cm and maximum of 250 cm.



## **Locking Points Bulletproof Door**

- 4 Central Security Bolts of the lock
- 1 Latch Bolt
- 4 Side Moving Bolts
- 1 Top Moving Bolt
- 1 Limiting Opening Device Bolt
- 5 Stable Security Bolts

### **Optional**

**Thermal - Sound** insulation through the internal fulfillment of the door leaf with incombustible thermal & sound insulating materials.



bulletporoof, security, fireproof and general use doors

Industrial Area Of Polykastro, P.O. Box: 23, P.C. 61200, Polykastro - Kilkis, Greece Tel.: +30 23430 20280 - 8, Fax: +30 23430 20289

e-mail: kete@kete-sa.gr

